



The **BTM Digital Grain Temp Monitor** will read and save to memory all your grain temperatures. This information may then be downloaded directly to your PC!

The BTM can store up to 10 readings. Once downloaded, the information may be compared with prior readings to see trends. It's your choice - view and print readings from ALL or only ONE of your grain temperature cables.

- High-contrast LCD screen is easy to read in sunlight or shade.
- The BTM is compatible with most existing thermocouple portable systems.
- Memory function eliminates the need for hand-written logs.
- Manual OHM/Resistance readings for evaluation of your temperature cables.
- Store information in your PC for evaluation of temperatures via USB connection.
- Stores and prints four readings from the BTM to compare and monitor temperature trends.
- Unlimited number of comparisons on your PC.
- Available for 6TC, 12TC & 18TC cables.
- Operates on four standard AA batteries.
- Real-time clock runs for 10 years on a separate battery.



## **SPECIFICATIONS**

BTM12 (12TC Jackhandle) BTM18 (18TC Jackhandle) LCD (Liquid Crystal Display) 4"W x 1"H

## **Temperature Measurements:**

C from -30 to +80 OHMS 10 to 1,000

Degrees F from -20 to +230

**GRAIN CONDITIONING** 

Thermocouple Sensor: Type T

Case Size: 8 1/2"W x 7"D x 3 1/2"H Battery Power: 4 Standard AA Batteries

Weight: 3 lbs.

Operating Temperature: 32° to 180°F/0° to 70°C

Capacity: Bins - Up to 30

Cables per Bin - Up to 60 TC's per Cable - Up to 21 Memory - last 10 readings.

P.O. Box 468 • 1600 Hudson Avenue West Spirit Lake, IA 51360

800-438-8367 • 712-336-0199 • Fax 712-336-0299 Email: TSGC@TSGCinc.com • www.TSGCinc.com